





Notes,

1.To maximize output force and life of linear actuators, radial load on lead screws should be avoided or be kept at a minimum.

CUSTOMER						NOTICE TO PERSONS RECEIVING THIS DRAWING THIS DRAWING IS ONLY CONDITIONALLY ISSUED, AND FOR THE SOLE PURPOSE OF INFORMING LICENSEES AND ASSOCIATE CONTRACTORS OF DINGS' MOTION, AND VENDORS THERETO AND CUSTOMERS THEREOF, RECEIPT OR POCESSION THEREOF DOES NOT CONFER TO TRANSFER ANY RIGHT IN THE SUBJECT MATTER OF THE DRAWING. THE DESIGN, CONSTRUCTION, TECHNICAL INFORMATION AND ALL OTHER SUBJECT MATTER SHOWN IN THIS DRAWING ARE AND REMAIN, EXCEPT AS MAY BE OTHERWISE INDICATED BY WRITTEN NOTICE HEREON, THE EXCLUSIVE PROPERTY OF SAID CORPORATION. THIS DRAWING MAY BE REPRODUCED ONLY BY LICENSEES														
WIRING CHART	EXCITATION SEQUENCE					AND ASSOCIATE CONTRACTORS OF SAID CORPORATION AND ONLY FOR LICENSED MANUFACTURE, AND BY VENDORS MANUFACTURING FOR SAID CORPORATION AND ONLY FOR LICENSEES AND ASSOCIATE CONTRACTORS.														
A+ M A- & &	CW	\longrightarrow				UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS AND TOLERANCES ARE AS BELOW PER ISO2768-ck.				DRAWN	Alice DATE 2020/11/12			DINCS						
	Red A+	+ -				LINEAR ANGULAR				APPRVD	DATE				DII4G2					
	Red/wht A-	-		+		0~3	±0.2	0 ~10	±1.5°			•	-						<u></u>	
	Green B+		+		-	3~6	±0.5	10 ~50		t				SIZE	А3	SHEET	1 OF 1			
	Grn/wht B-		-		+					MODEL		8N21-100			-			-[-	-(⊕)-	
	CCW	\leftarrow				6 ∼30	±0.8	50 ~120	±30′	4				SCALE	1. 1	REV	00		Ý	
						30 ∼120	±1.5	120 ~400	±15′		1			I SCALL	I	KEV	00	i	•	